

Gardner
Denver

ROTARY COMPRESSORS | AIR TREATMENT

Total Solution Provider



Gardner Denver

provides the broadest range of air compressors that handle a wide-variety of applications. From the most demanding, requiring compressed air 24/7/365 to the fluctuating day-to-day or shift-to-shift, we have the right compressor to maximize productivity and energy savings.

FIXED SPEED | OIL-FLOODED ROTARY COMPRESSORS



hydrovane

Versatile

- 2-60 HP
- 100-150 PSIG
- 4.5-226 CFM



Apex

Peak Performance

- 5-25 HP
- 110-175 PSIG
- 18-110 CFM



L Series

Simplistic

- 10-180 HP
- 75-190 PSIG
- 26-800 CFM



Electra-Screw

Trusted Value

- 40-50 HP
- 85-175 PSIG
- 148-185 CFM



Electra-Saver II

Slow Speed Reliability

- 30-200 HP
- 85-200 PSIG
- 58-1000 CFM



Electra-Saver

Turn-Valve Efficiency

- 50-500 HP
- 85-150 PSIG
- 200-2459 CFM

VARIABLE SPEED | OIL-FLOODED ROTARY COMPRESSORS



hydrovane

Investment Effective


- 7-45 kW
- 100-150 PSIG
- 33-264 CFM



Apex VS

Variable Speed Efficiency

- 7-22 kW
- 110-175 PSIG
- 38-145 CFM



LRS Series

Energy Efficiency

- 7-132 kW
- 75-190 PSIG
- 29-1465 CFM



VS Series

Constant Efficiency

- 20-250 kW
- 100-175 PSIG
- 108-1553 CFM



VST Series

Ultimate Efficiency

- 55-260 kW
- 100-175 PSIG
- 389-2032 CFM

OIL-FREE | COMPRESSORS



ISO CLASS : 0
PLUS SILICONE FREE
ISO 8573-1 (2010)



EnviroAire VS

- 15-110 kW
- 75-145 PSIG
- 78-655 CFM



EnviroAire TVS

- 110-160 kW
- 115-145 PSIG
- 316-826 CFM



EnviroAire T

- 75-160 kW
- 115-145 PSIG
- 457-788 CFM



Quantima

- 150-300 kW
- 750-1860 CFM

WARRANTY PROGRAMS

Gardner Denver offers industry leading warranty programs that allow our customers to decide which option works best for them. Whether its 5 or 10 years, we have a warranty program that works for you.



REFRIGERATED DRYERS

Non-Cycling

RNC Series

- 10–3000 CFM
- Integrated Grade B Filter
- Cold Coalescing Filter Option
- Zero-Loss Drain

Energy Saving

RES / RSD Series

- 90–675 CFM (RES)
- 800–3000 (RSD)
- Integrated Grade B Filter
- Cold Coalescing Filter Option
- Zero-Loss Drain

High Temp/High Pressure

RHT/RHP Series

- 20–125 CFM (RHT)
- 180° F High Inlet Temperature (RHT)
- 30–300 CFM (RHP)
- 725 PSIG High Pressure (RHP)
- Integrated Grade B Filter
- Zero-Loss Drain

DESICCANT & MEMBRANE DRYERS

Desiccant Heatless

DGH Series

- 40–5400 CFM
- Dewpoint to -100° F
- Mounted Filter Packages
- Small Footprint
- Consistent Dewpoint

Desiccant Externally Heated

DHP/DPB Series

- 300–4300 CFM
- Dewpoint to -40° F
- Mounted Filter Packages
- Energy Management Feature
- Critical Use Air Treatment

Membrane

MES/MMD Series

- 1.5–138 CFM
- Dewpoint to -40° F
- No Power Source Needed
- Point-of-use Installation
- Optional Digital Purge Control

FILTERS, SEPARATORS, DRAINS, PIPING, LUBRICANTS & WARRANTIES

Filters

FIL Series

- 20–21,250 CFM
- ISO Quality Classes 1 to 6
- Multiple Drain & Indicator Options

FHP Series

- 20–21,250 CFM
- Pressures up to 900 PSIG
- Interfaces with RHP Series Dryers
- Grade B to F Filtration Options

FHT Series

- 100–11,400 CFM
- Inlet Temperatures to 450° F
- Ideal For Post Desiccant Filtration

Oil/Water Separators

CTS/CTS-T

- Effectively Treats Contaminated Compressor Condensate

Lubricants

AEON Lubricant

- 8,000 hour Synthetic Blends
- Food Grade
- Biodegradable Blends
- High Temperature Blends

Compressed Air Tubing

Quick-Lock/Big Lock

- Sizes from 0.5–8"
- Extruded Aluminium Piping
- All Metal Fittings
- Colors in Blue, Grey, & Black

Drains

SMD Series

- Zero-Loss Pneumatic

EDDS Series

- Zero-Loss Demand
- AED Series
- Electric Timed Drain



The leader in every market we serve
by continuously improving all business processes
with a focus on innovation and velocity

Gardner Denver

Gardner Denver, Inc.

1800 Gardner Expressway
Quincy, IL 62305
866-440-6241

www.gardnerdenverproducts.com

©2015 Gardner Denver, Inc. Printed in U.S.A.
GS-LINE 4th Ed. 4/15

 Please recycle after use.

